



Soundproofing America Online Store
“Soundproofing from Coast to Coast”

Toll Free Line: 877-530-0139

West Coast Number: 760-510-9189

East Coast Number: 347-328-0501

Fax: 760-571-5007

AMERICAN IMPACT STANDARD™



- **3/8” Thick**
- **48”wide x 25’ long Sound Reduction Roll**
- **1.4 Lbs per Square Ft**
- **Recycled Rubber**
- **Green Product**
- **Durable, Long-Lasting**
- **Maximum Impact Protection**
- **Heavy Sound Barrier**
- **Excellent Floor to Floor soundproofing**
- **Great under Hardwood, Ceramic or Carpet**
- **Can be Adhesive, Nailed or Screwed**

FLOOR/CEILING ASSEMBLIES:

Carpet and Pad Assembly

CARPET AND PAD
 3/8” THICK
 AMERICAN IMPACT
 STD
 RUBBER TO WOOD
 ADHESIVE
 3/4” PLYWOOD SUB
 FLOOR
 18” DEEP OPEN
 FLOOR TRUSSES
 6” BATT INSULATION
 5/8” GYSUM ON
 RESILIENT CHANNEL

STC 70 IIC 70

Ceramic Floor Assembly

CERAMIC TILE
 3/8” THICK
 AMERICAN IMPACT
 STD
 RUBBER TO WOOD
 ADHESIVE
 3/4” PLYWOOD SUB
 FLOOR
 18” DEEP OPEN FLOOR
 TRUSSES
 6” BATT INSULATION
 5/8” GYSUM ON
 RESILIENT CHANNEL

STC 59 IIC 55

Wood Floor Assembly

WOOD FLOOR
 3/8” THICK
 AMERICAN IMPACT
 STD
 RUBBER TO WOOD
 ADHESIVE
 3/4” PLYWOOD SUB
 FLOOR
 18” DEEP OPEN
 FLOOR TRUSSES
 6” BATT INSULATION
 5/8” GYSUM ON
 RESILIENT CHANNEL

STC 59 IIC 55