



Soundproofing America Online Store
Your #1 Soundproofing Source Worldwide

Toll Free Line: 877-530-0139

West Coast Number: 760-510-9189

East Coast Number: 347-328-0501

Fax: 760-571-5007



Americatek Pyramid Panel™

**Melamine Foam
 Sound Absorber**

- *High Performance Absorber*
- *Increased Absorptive Surface Area*
- *Fiber Free*
- *Class A Fire Retardant*

MATERIAL: Open Cell Melamine Acoustical Foam.

PATTERN: Pyramid for Monolithic Appearance.

FEATURES: Increased Surface Area, High Performance, Light Weight, Dramatic Visual Effect.

APPLICATIONS: Ceilings, Walls, Industrial, Commercial & Home Audio Markets, Broadcasting and Recording Studios.

THICKNESS: 2", 3", 4" and Custom.

SIZES: 2' x 2', 2' X 4' (Custom Sizes Available).

DENSITY: 0.7 lbs./cub. ft.

COLOR: Natural White, Latex or Cleanable Dupont Hypalon Paint - Black, Light Grey, Almond, White (Custom Colors also Available).

FLAMMABILITY: ASTM E-84, Class 1. Flame Spread: 5; Smoke Developed: 50.

INSTALLATION: Acoustical Adhesive.

Sound Absorption/Noise Reduction per ASTM C423-90a							
	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
2"	0.07	0.25	0.60	0.94	0.97	1.08	0.70
4"	0.18	0.44	0.96	1.14	1.18	1.19	0.95
6"	0.16	0.62	1.10	1.20	1.21	1.22	1.05

