



Give us a call to help you determine if American Melamine Panels are the right material for your particular use. We are here to assist you with information and pricing at our toll free number:

**(877) 530-0139**

**Soundproofing America Online Store**  
**"Soundproofing From Coast to Coast"**  
 Toll Free Line: **877-530-0139**  
 West Coast Number: **760-510-9189**  
 East Coast Number: **347-328-0501**  
 Fax: **760-571-5007**

## American Melamine Pyramid Panels™

**Class-one flame-resistant American Melamine foam panels—high-temperature applications**

American Melamine foam is an excellent noise absorbing material and is rated for high-temperature applications or those requiring **Class 1** rated materials. Heat resistant to 482°F and able to withstand constant temperatures up to 320°F, American Melamine Foam is engineered for environments where temperatures are high, sparks or other hot materials may fly, large numbers of people congregate, or where building code requires fire-rated materials.

American Melamine material is a porous acoustical melamine. The internal structure is a spacious cellular complex of slim, flexible webs that are membrane-free and completely open-celled. The result is a lightweight and easy-to-install material.

American Melamine is approved as a Class 1 building material and is also resistant to many chemicals. Panels come in three different colors—natural white, light gray and charcoal. The charcoal colored product additionally meets the European flame standard. In addition, we can paint American Melamine panels with two different types of paint:

1. Standard latex—we can match any color
2. Multi-Spec latex—great for the theatre room or for that extra splash of color

Products that are constructed of American Melamine include:

Pyramid Panels are available in 2", 3", 4" thick varieties.

FIREFLEX PYRAMID DESIGN							
Size:	24" x 24"						
Thicknesses:	2", 3", 4"						
Density:	0.7 lb/cubic foot						
Flammability:	Class 1						
Flame spread:	10						
Smoke density:	50						
Colors:	natural white, light gray, charcoal						
Frequency (Hz)	125	250	500	1K	2K	4K	NRC
TFPX-2	.09	.28	.79	.94	1.00	1.04	.75
TFPX-3	.10	.48	.91	1.11	1.11	1.14	.90
TFPX-4	.16	.56	1.11	1.13	1.13	1.21	1.00