

SOUNDPROOFING AMERICA, INC.

SOUND VAULT DOORS-INTERIOR ACOUSTICAL-SOUNDPROOF DOORS

SECTION 08347 – SOUND CONTROL DOORS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes sound control doors with STC ratings up to 56.

1.3 SUBMITTALS

- A. Product Data: Submit manufacturer's product data and installation instructions.
- B. Test Reports: Upon request submit certified test reports from recognized test laboratories.
- C. Certificates: Submit manufacturer's certificate that products meet or exceed specified requirements.

1.4 DELIVERY, STORAGE & HANDLING

- A. Delivery: Deliver material in the manufacturer's original, unopened, undamaged containers with identification labels intact.
- B. Provide labels indicating brand name, source of procurement, style, size and thickness.
- C. Storage and Protection: Store materials protected from exposure to harmful environmental conditions and at temperature and humidity conditions recommended by the manufacturer.

1.5 WARRANTY

- A. Warranty Period: Two years.

## PART 2 - PRODUCTS

### 2.1 MANUFACTURERS

#### A. Sound Control Doors:

1. Sound Vault Interior Doors by Soundproofing America Inc. (Basis of Design)
  - a. 141 North Pacific Street, Suite E.
  - b. San Marcos, CA 92069.
  - c. (877) 530-0139
  - d. [www.SoundproofingAmerica.com](http://www.SoundproofingAmerica.com)
2. Or equal.

### 2.2 SOUND CONTROL DOORS

#### A. STC ratings: Up to 56 per ASTM E-90.

#### B. Door Thickness: 2-3/4" thick, 13 layer composite door assembly.

#### C. Pre-hung and Assembly:

1. Door: **[Flush design] [Custom] [With vision elites] [Single] [Pairs] [As indicated on Drawings].**
2. Frame: **[Standard frame] [Custom] [As indicated on Drawings].**

#### D. Sizes: **[Select from standard] [Custom pairs up to 8' w x 10' h] [As indicated on Drawings].**

#### E. Finishes: Stain grade in **[Oak] [Maple] [Cherry] [Birch] [Primed Metal] [Any wood species as selected by Architect].**

#### F. Hardware: Door, frame, trim, handle, hinges, perimeter sound seals and door bottom supplied as part of the tested assembly.

1. Automatic sill.
2. Heavy duty hinges (4).
3. 3-point latching system.
4. Adjustable neoprene mortise jams and seals.
5. Options: **[Dead bolt] [Mortise locks] [Heavy duty closer].**
6. Finishes: **[Standard nickel] [Standard brass] [Custom as selected by Architect].**

#### G. **[Optional Vision Lite Kit]: [Metal] [Wood].**

1. **Clear glass opening size: [10" x 10"] [6" x 28"] [22" x 28"] [Custom].**

#### H. **[Optional Jamb Kit].**

#### I. Required Installation kit Includes:

1. 2 Packs of Shims.
2. 4 Sets of Heavy Duty Jamb Screws.
3. Backer Rod.
4. 1 Tube Acoustical Sealant.

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Examine openings, substrates, anchorage, and conditions.
- B. Immediately inspect shipment for damage during transit i.e., damage caused by fork lifts, stacking, water stains etc. and disclose to delivery driver prior to signing for receipt.

### 3.2 INSTALLATION

- A. Manufacturer's Instructions:
  - 1. Comply with written instructions and of the door manufacturer.
  - 2. Installation manual is available from manufacturer's website.

END OF SECTION 08347