

Soundproofing America Online Store

“Soundproofing from Coast to Coast”

Toll Free Line: **800-823-6817**

West Coast Number: **760-888-7515**

East Coast Number: **347-328-0501**



- **3/8” Thick**
- **Roll Size 48”x25’**
- **1.4 Lbs per Square Ft**
- **Recycled Rubber**
- **Green Product**
- **Durable, Long-Lasting**
- **Maximum Impact Protection**
- **Heavy Sound Barrier**
- **Excellent Floor to Floor soundproofing**
- **Great under Hardwood, Ceramic or Carpet**
- **Can be Adhesive, Nailed or Screwed**

FLOOR/CEILING ASSEMBLIES:

Carpet and Pad Assembly

CARPET AND PAD
 3/8” THICK MED DENSITY AMERICAN IMPACT STD
 RUBBER TO WOOD ADHESIVE
 3/4” PLYWOOD SUB FLOOR
 18” DEEP OPEN FLOOR TRUSSES
 6” BATT INSULATION
 5/8” GYSUM ON RESILIENT CHANNEL

STC 70 IIC 70

Ceramic Floor Assembly

CERAMIC TILE
 3/8” THICK MED DENSITY AMERICAN IMPACT STD
 RUBBER TO WOOD ADHESIVE
 3/4” PLYWOOD SUB FLOOR
 18” DEEP OPEN FLOOR TRUSSES
 6” BATT INSULATION
 5/8” GYSUM ON RESILIENT CHANNEL

STC 59 IIC 55

Wood Floor Assembly

WOOD FLOOR
 3/8” THICK MED DENSITY AMERICAN IMPACT STD
 RUBBER TO WOOD ADHESIVE
 3/4” PLYWOOD SUB FLOOR
 18” DEEP OPEN FLOOR TRUSSES
 6” BATT INSULATION
 5/8” GYSUM ON RESILIENT CHANNEL

STC 59 IIC 55

