



## **Soundproofing America Online Store** **“Soundproofing from Coast to Coast”**

**Toll Free Line: 800-823-6817**

**West Coast Number: 760-888-7515**

**East Coast Number: 347-328-0501**



- **3/8” Thick**
- **23”x42” Sound Reduction Tiles**
- **2.2 Lbs per Square Ft**
- **Recycled Rubber**
- **Green Product**
- **Durable, Long-Lasting**
- **Maximum Impact Protection**
- **Heavy Sound Barrier**
- **Excellent Floor to Floor soundproofing**
- **Great under Hardwood, Ceramic or Carpet**
- **Can be Adhesive, Nailed or Screwed**

### **FLOOR/CEILING ASSEMBLIES:**

#### ***Carpet and Pad Assembly***

CARPET AND PAD

3/8” THICK MED DENSITY AMERICAN IMPACT STD

RUBBER TO WOOD ADHESIVE

3/4” PLYWOOD SUB FLOOR

18” DEEP OPEN FLOOR TRUSSES

6” BATT INSULATION

5/8” GYSUM ON RESILIENT CHANNEL

**STC 70 IIC 70**

#### ***Ceramic Floor Assembly***

CERAMIC TILE

3/8” THICK MED DENSITY AMERICAN IMPACT STD

RUBBER TO WOOD ADHESIVE

3/4” PLYWOOD SUB FLOOR

18” DEEP OPEN FLOOR TRUSSES

6” BATT INSULATION

5/8” GYSUM ON RESILIENT CHANNEL

**STC 59 IIC 55**

#### ***Wood Floor Assembly***

WOOD FLOOR

3/8” THICK MED DENSITY AMERICAN IMPACT STD

RUBBER TO WOOD ADHESIVE

3/4” PLYWOOD SUB FLOOR

18” DEEP OPEN FLOOR TRUSSES

6” BATT INSULATION

5/8” GYSUM ON RESILIENT CHANNEL

**STC 59 IIC 55**

