



Soundproofing America Online Store "Soundproofing from Coast to Coast"

Toll Free Line: **800-823-6817**

West Coast Number: **760-888-7515**

East Coast Number: **347-328-0501**



Give us a call to help you determine if Maximum Acoustics Panel is the right product for your particular use. We are here to assist, please call:
(800) 823-6817

Maximum Acoustics Panel™

POLYESTER ACOUSTICAL WALL AND CEILING TILES

- Formaldehyde Free
- No Binding Agents
- No Chemical Irritants
- Architecturally Decorative
- Tackable Surface
- Class A Fire Rated: Flame Spread=15, Smoke Develop=250
- 60% Polyethylene Terephthalate- Recycled
- Material: 7.5# per cubic foot density panels made from 100% polyester
- Applications include Theaters and Home Theaters, Gymnasiums & Multipurpose Room, Commercial and Office Buildings, Studios & Production Houses, Restaurants & Night Clubs, Government & Municipal Buildings, Schools & Universities, Industrial & Manufacturing Facilities.
- Sizes: White 23 ¾" x 47 ¾" & 48"x96", Dark Beige 24"x48" available in 23 ¾" x 47 ¾" in black/white combo for grid ceilings

	Size	Mount	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
Maximum Acoustics Panel	1" Thick	adhesive	.08	.20	.59	.94	1.04	1.02	.70

	Size	Mount	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
Maximum Acoustics Panel	1" Thick	Ceiling grid	.44	.80	.99	1.00	.97	.90