

POLYZORBE

SPEC SHEET

- ✓ Architecturally Decorative
- ✓ Controls Echo & Reverb
- ✓ No Formaldehyde
- ✓ No Chemical Irritants
- ✓ Custom Graphics



Material:	Polyester (60% Recycled)
Patterns:	Fibrous, Semi-Rigid
Features:	Decorative, Lightweight, Tackable Surface, Non-Toxic, Non-Allergenic, Fungal Resistant, Ceiling Tile Option
Application:	Homes, apartments, recording studios, hotels, conference rooms, offices, music rooms, houses of worship, community centers, hospitals, auditoriums, malls, retail stores, schools, restaurants, bars
Thickness:	1" & 2"
Sizes:	24" x 24", 24" x 48", 48" x 96"
Colour:	White, Beige, Black
Flammability:	ASTM E84, Class A Flame Spread: 15 Smoke Developed: 250
Installation:	Acoustical Adhesive

Sound Absorption / Noise Reduction Coefficient

Size	Mount	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
1" Thick	Wall Mounted	0.08	0.20	0.59	0.94	1.04	1.02	0.70
2" Thick	Wall Mounted	0.31	0.58	1.08	1.11	1.04	1.04	0.95

